M16 A4 Practical

Student	Name:	Date:	
Instructor:		Grade:	
Disass	embly/Field Strip		
1.	Make sure weapon is on safe (state weapon is on safe and show proctor)		Ye

- s/No 2 points Yes/No 2 points 2. Depress the magazine release button
- 3. Pull the charging handle rearward and lock bolt in place by pressing on the bolt catch
- 4. Visually inspect the upper receiver and chamber or any ammunition
- 5. Clear Weapon (show and state weapon is clear to proctor)

- Yes/No 2 points
- 6. Press the upper portion of the bolt release to allow bolt to slide forward
- 7. Place the selector lever on Safe and close the ejection port cover
- 8. Pop out the rear takedown pin
- 9. Swing the receivers apart for inner access
- 10. Pull the charging handle rearward on the upper receiver
- 11. Pull the bolt carrier group out of the upper receiver
- 12. Remove the charging handle
- 13. Separate the upper receiver from the lower receiver
- 14. Remove the buffer assembly and action spring from the lower receiver

Reassembly

- 1. Insert the charging handle back into the upper receiver (do not push forward all the way) Yes/No 2 points
- 2. Install the bolt carrier group into the upper receiver onto the charging handle make sure the bolt assembly is pulled
- Push the bolt and charging handle forward fully until they lock in place 3.
- 4. Close ejection port cover
- Bring upper and lower recvier together and push the rear takedown pin back

Functions Check

- Place weapon on saf(state weapon is on safe and show proctor)
- If it will not go on safe, pull charging handle back fully and then let go to release bolt forward
- 3. Place on safe
- 4. Pull the trigger to the rear (hammer should NOT fall, click should NOT be heard)
- Place the safety selector on SEMI.
- Pull trigger to the rear again, holding in place (hammer SHOULD fall, SHOULD hear a click 6.
- 6. Insert guide rod into the spring Yes/No 2 points 7. Reinsert guide rod with spring into barrel Yes/No 2 points Reinsert slide back onto pistol Yes/No 2 points Push slide back and lift up the disassembly latch Yes/No 2 points 10. Push slide back and check to see if locks back Yes/No 2 points 11. Check safety latch for on and off position Yes/No 2 points